

Date revised: 17.05.2023

Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Hardener S for cds-Mortar 0-3 L flex special

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Coating material

## 1.3. Details of the supplier of the safety data sheet

#### Address/Manufacturer

cds Polymere GmbH & Co. KG Gau-Bickelheimer Str. 72 55576 Sprendlingen/Rhh.

Telephone no. +49(6701) 9350-0 Fax no. +49(6701) 9350-50

#### 1.4. Emergency telephone number

cds-Labor / Tel. +49 (67 01) 93 50-28 (This number is reachable monday to friday from 8 am to 5 pm)

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Skin Corr. 1A H314 Eye Dam. 1 H318 Skin Sens. 1A H317 Repr. 2 H361fd STOT SE 3 H335 STOT RE 1 H372 Asp. Tox. 1 H304 Aquatic Acute 1 H400 H410 Aquatic Chronic 1

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008 For explanation of abbreviations see section 16.

#### 2.2. Label elements

## Labelling according to regulation (EC) No 1272/2008

### **Hazard pictograms**



#### Signal word

Danger

#### **Hazard statements**

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.



Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.
H410 Very toxic to aquatic life with long lasting effects.

**Precautionary statements** 

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains 2-Piperazin-1-ylethylamin; Reaction mass of (1-Phenylethyl)phenols and bis-(1-

phenylethyl)phenols; Amines, coco alkyl; (Z)-octadec-9-enylamine;

Polyoxypropylendiamin

#### 2.3. Other hazards

No special hazards have to be mentioned.

# **SECTION 3: Composition/information on ingredients**

#### **Hazardous ingredients**

#### (Z)-octadec-9-enylamine

CAS No. 112-90-3 EINECS no. 204-015-5

Registration no. 01-2119473797-19-XXXX

Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H302
Asp. Tox. 1 H304
Skin Corr. 1B H314
STOT SE 3 H335
STOT RE 2 H373
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 M = 10Aquatic Chronic M = 10

1

Reaction mass of (1-Phenylethyl)phenols and bis-(1-phenylethyl)phenols

EINECS no. 701-443-9

Registration no. 01-2119980970-27-XXXX

Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Skin Irrit. 2 H315 Skin Sens. 1A H317 Aquatic Chronic 2 H411

Polyoxypropylendiamin

CAS No. 9046-10-0 EINECS no. 618-561-0

Registration no. 01-2119557899-12-XXXX

Concentration >= 10 < 25 %



Print date: 17.05.2023

Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB

Classification (Regulation (EC) No. 1272/2008)

Skin Corr. 1C H314 Eye Dam. 1 H318 Aquatic Chronic 3 H412

2-Piperazin-1-ylethylamin

CAS No. 140-31-8 EINECS no. 205-411-0

Registration no. 01-2119471486-30-XXXX

Concentration >= 10 < 25 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3 H311 Repr. 2 H361 STOT RE 1 H372 Skin Corr. 1B H314 Eye Dam. 1 H318 Acute Tox. 4 H302 Skin Sens. 1 H317 Aquatic Chronic 3 H412

**Urethane Prepolymer** 

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H302

Amines, coco alkyl

CAS No. 61788-46-3 EINECS no. 262-977-1

Registration no. 01-2119473798-17-XXXX

Concentration >= 3 < 5 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H302
Asp. Tox. 1 H304
Skin Corr. 1B H314
STOT SE 3 H335
STOT RE 2 H373
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 M = 10Aquatic Chronic M = 10

1

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Remove contaminated, soaked clothing immediately and dispose of safely. Adhere to personal protective measures when giving first aid. Clean body thoroughly (bath, shower). In any case show the physician the Safety Data Sheet.

#### After inhalation

Ensure supply of fresh air. Remove affected person from danger area. Seek medical advice immediately.

#### After skin contact



Date revised: 17.05.2023

Print date: 17.05.2023

Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB

Substance number: 10292 Replaces Version: - / GB

Wash off immediately with soap and water. Seek medical advice immediately.

#### After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Take medical treatment.

#### After ingestion

Call in a physician immediately and show him the Safety Data Sheet. Rinse mouth thoroughly with water. Let plenty of water be drunk in small gulps. Do not induce vomiting.

# Adhere to personal protective measures when giving first aid

First aider: Pay attention to self-protection!

## 4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

# 4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / hazards

In the case of swallowing with subsequent vomiting, aspiration of the lungs can occur which can lead to chemical pneumonia or asphyxiation.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

#### Suitable extinguishing media

Dry powder

#### Non suitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

In case of combustion evolution of dangerous gases possible.

#### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighting

Do not inhale explosion and/or combustion gases. In case of combustion use a suitable breathing apparatus. Wear full protective suit.

#### Other information

Collect contaminated fire-fighting water separately, must not be discharged into the drains. Fire residues and contaminated fire-fighting water must be disposed of in accordance with the local regulations. Observe manufacturer's / distributor's instructions.

# SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use breathing apparatus if exposed to vapours/dust/aerosol. Avoid contact with skin, eyes and clothing. Refer to protective measures listed in Sections 7 and 8.

#### 6.2. Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Retain and dispose of contaminated wash water. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

Pick up with absorbent material. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Containers in which spilt substance has been collected must be adequately labelled. Dispose of absorbed material in accordance with the regulations.



Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid formation of aerosols. Perform filling operations only at stations with exhaust ventilation facilities. Provide suitable exhaust ventilation at the processing machines. If workplace limits are exceeded, a respiratory protection approved for this particular job must be worn. Keep container tightly closed.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in original packaging, tightly closed. Storage rooms must be properly ventilated. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Provide solvent-resistant and impermeable floor.

#### Hints on storage assembly

Do not store together with foodstuffs.

### Storage classes

Storage class according to TRGS 510 8

Corrosive hazardous substances

#### Further information on storage conditions

Do not keep at temperatures above 20 °C.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Other information

Contains no substances with occupational exposure limit values.

#### Derived No/Minimal Effect Levels (DNEL/DMEL)

2-Piperazin-1-ylethylamin

Reference substance 2-Piperazin-1-ylethylamin
Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 10,6 mg/m³

2-Piperazin-1-ylethylamin

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Concentration

Worker

Acute
inhalative

Systemic effects

10.6

Concentration 10,6 mg/m³

2-Piperazin-1-ylethylamin

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Local effects



Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

Concentration 0,015 mg/m³

2-Piperazin-1-ylethylamin

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Short term
Route of exposure inhalative
Mode of action Local effects

Concentration 0,08 mg/m<sup>3</sup>

2-Piperazin-1-ylethylamin

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 3,33 mg/kg/d

2-Piperazin-1-ylethylamin

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Short term
Route of exposure dermal

Mode of action Systemic effects

Concentration 20 mg/kg/d

Reaction mass of (1-Phenylethyl)phenols and bis-(1-phenylethyl)phenols

Reference substance Reaction mass of (1-Phenylethyl)phenols and bis-(1-

phenylethyl)phenols

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 2,87 mg/kg

Reaction mass of (1-Phenylethyl)phenols and bis-(1-

phenylethyl)phenols

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 1,21 mg/m³

Amines, coco alkyl

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Worker

Long term

inhalative

Systemic effects

Concentration 0,38 mg/m³

**Predicted No Effect Concentration (PNEC)** 

2-Piperazin-1-ylethylamin

Reference substance 2-Piperazin-1-ylethylamin



Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

Type of value PNEC
Type Freshwater

Concentration 0,058 mg/l

2-Piperazin-1-ylethylamin

Type of value PNEC Type Marine

Concentration 0,0058 mg/l

2-Piperazin-1-ylethylamin

Type of value PNEC

Type Water (intermittent release)

Concentration 0,58 mg/l

2-Piperazin-1-ylethylamin

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 250 mg/l

2-Piperazin-1-ylethylamin

Type of value PNEC Sediment

Concentration 215 mg/kg

2-Piperazin-1-ylethylamin

Type of value PNEC

Type Marine sediment

Concentration 21,5 mg/kg

2-Piperazin-1-ylethylamin

Type of value PNEC Type Soil

Concentration 1 mg/kg

Reaction mass of (1-Phenylethyl)phenols and bis-(1-phenylethyl)phenols

Reference substance Reaction mass of (1-Phenylethyl)phenols and bis-(1-

phenylethyl)phenols

Type of value PNEC
Type Freshwater

Concentration 0,0115 mg/l

Reaction mass of (1-Phenylethyl)phenols and bis-(1-

phenylethyl)phenols

Type of value PNEC
Type Marine

Concentration 0,00115 mg/l

Amines, coco alkyl

Reference substance Amines, coco alkyl

Type of value PNEC Freshwater

Concentration 0,00026 mg/l

Amines, coco alkyl

Type of value PNEC Type Marine

Concentration 0,000026 mg/l



Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

Amines, coco alkyl

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 0,55 mg/l

Amines, coco alkyl

Type of value PNEC

Type Freshwater sediment

Concentration 0,1794 mg/kg

Amines, coco alkyl

Type of value PNEC

Type Marine sediment

Concentration 0,01794 mg/kg

Amines, coco alkyl

Type of value PNEC Type Soil

Concentration 10 mg/kg

#### 8.2. Exposure controls

#### General protective and hygiene measures

Hold emergency shower available. Hold eye wash fountain available. Do not inhale gases/vapours/aerosols. Avoid contact with skin and eyes. Do not eat, drink or smoke during work time. Storage of foodstuffs in work rooms is forbidden. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

# Respiratory protection

If workplace limits are exceeded, a respiratory protection approved for this particular job must be worn.

#### Hand protection

Chemical resistant gloves

Appropriate Material neoprene

#### Eye protection

Safety glasses with side protection shield; Face shield

#### **Body protection**

Clothing as usual in the chemical industry. Protective shoes

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state liquid

**Melting point** 

Remarks not determined

Freezing point

Remarks not determined

# Boiling point or initial boiling point and boiling range

Remarks not determined

**Flammability** 

evaluation not determined

#### Upper and lower explosive limits

Remarks not determined



Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

Flash point

Value > 100 °C

Ignition temperature

Remarks not determined

**Decomposition temperature** 

Remarks not determined

pH value

Remarks not determined

**Viscosity** 

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Remarks not determined

Density and/or relative density

Value 0,93 g/cm<sup>3</sup>

Temperature 23 °C

Relative vapour density

Remarks not determined

9.2. Other information

**Odour threshold** 

Remarks not determined

**Evaporation rate (ether = 1):** 

Remarks not determined

Solubility in water

Remarks not determined

**Explosive properties** 

evaluation not determined

**Oxidising properties** 

Remarks not determined

Other information

None known

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

#### 10.2. Chemical stability

No hazardous reactions known.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions known.

#### 10.4. Conditions to avoid

No hazardous reactions known.



Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

#### 10.5. Incompatible materials

None known

#### 10.6. Hazardous decomposition products

Toxic gases/vapours, Irritant gases/vapours

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute oral toxicity** 

ATE 1.153,37 mg/kg

04

Method calculated value (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Acute oral toxicity (Components)** 

2-Piperazin-1-ylethylamin

Reference substance Ethylbenzene

Species rat

LD50 2140 mg/kg

Reaction mass of (1-Phenylethyl)phenols and bis-(1-phenylethyl)phenols

Species rat

LD50 > 2000 mg/kg

Method OECD 423

Amines, coco alkyl

Species rat

LD50 > 300 to 2000 mg/kg

Polyoxypropylendiamin

Species rat

LD50 2885 mg/kg

Method OECD 401

Acute dermal toxicity

ATE 6.357,36 mg/kg

31

Method calculated value (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Acute dermal toxicity (Components)** 

2-Piperazin-1-ylethylamin

Reference substance 2-Piperazin-1-ylethylamin

Species rabbit

LD50 866 mg/kg

Reaction mass of (1-Phenylethyl)phenols and bis-(1-phenylethyl)phenols

Species rat

LD50 > 2000 mg/kg

Method OECD 402

Polyoxypropylendiamin

Species rabbit

LD50 2980 mg/kg

Method OECD 402

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

**Acute inhalative toxicity (Components)** 



Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

#### Reaction mass of (1-Phenylethyl)phenols and bis-(1-phenylethyl)phenols

Species rat

LC0 4,9 mg/l

Duration of exposure 4 h

Administration/Form Dust/Mist Method OECD 403

#### Skin corrosion/irritation

evaluation corrosive

Remarks The classification criteria are met.

#### Skin corrosion/irritation (Components)

Amines, coco alkyl

Species rabbit evaluation corrosive

#### Serious eye damage/irritation

evaluation corrosive

Remarks The classification criteria are met.

Sensitization

evaluation May cause sensitization by skin contact. Remarks The classification criteria are met.

#### Subacute, subchronic, chronic toxicity

Remarks not determined

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

evaluation Suspected of damaging fertility. Suspected of damaging the unborn child.

Remarks The classification criteria are met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

#### Specific Target Organ Toxicity (STOT)

Single exposure

Remarks The classification criteria are met. evaluation May cause respiratory irritation.

Repeated exposure

Remarks The classification criteria are met.

evaluation Causes damage to organs through prolonged or repeated exposure

# **Specific Target Organ Toxicity (STOT) (Components)**

Amines, coco alkyl

evaluation May cause respiratory irritation.

#### Aspiration hazard

The classification criteria are met.

Harmful: may cause lung damage if swallowed.

## 11.2 Information on other hazards

#### **Experience in practice**

Inhalation may lead to irritation of the respiratory tract.

#### Other information

No toxicological data are available.

# **SECTION 12: Ecological information**



Date revised: 17.05.2023

Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

# 12.1. Toxicity

#### **General information**

not determined

#### Fish toxicity (Components)

#### 2-Piperazin-1-ylethylamin

Species Fathead minnow (Pimephales promelas) LC50 2190 mg/l

Duration of exposure 96 h

#### Reaction mass of (1-Phenylethyl)phenols and bis-(1-phenylethyl)phenols

Species zebra fish (Brachydanio rerio)

LL50 14,8 mg/l

Duration of exposure 96 h

Method OECD 203

#### Amines, coco alkyl

Reference substance Amines, coco alkyl

Species Fathead minnow (Pimephales promelas)
LC50 > 0,01 to 0,1 mg/l

#### Polyoxypropylendiamin

Species rainbow trout (Oncorhynchus mykiss)

EC50 > 15 mg/l

Duration of exposure 96 h

#### **Daphnia toxicity (Components)**

#### 2-Piperazin-1-ylethylamin

Species Daphnia magna

EC50 58 mg/l

Duration of exposure 48 h

#### Reaction mass of (1-Phenylethyl)phenols and bis-(1-phenylethyl)phenols

Species Daphnia magna

EC50 4,6 mg/l

Duration of exposure 48 h

Method OECD 202

#### Amines, coco alkyl

Reference substance Amines, coco alkyl

Species Daphnia magna

EC50 > 0,01 to 0,1 mg/l

Duration of exposure 48 h

# Amines, coco alkyl

Reference substance Amines, coco alkyl

Species Daphnia magna

NOEC > 0,01 to 0,1 Duration of exposure 21 Days

Method OECD 211

#### Polyoxypropylendiamin

Species Daphnia magna

EC50 80 mg/l

Duration of exposure 48 h

Method OECD 202

#### Algae toxicity (Components)

#### 2-Piperazin-1-ylethylamin

Species Pseudokirchneriella subcapitata

EC50 > 1000 mg/l

Duration of exposure 72 h



Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB Print date: 17.05.2023

Reaction mass of (1-Phenylethyl)phenols and bis-(1-phenylethyl)phenols

Species Scenedesmus subspicatus

EL50 3,14 mg/l

Duration of exposure 72 h

Method **OECD 201** 

Amines, coco alkyl

Reference substance Amines, coco alkyl

Species Scenedesmus subspicatus

EC50 0.01 to 0,1 mg/l Duration of exposure

72

Polyoxypropylendiamin

Species Selenastrum capricornutum

ErC50 15 mg/l

72 Duration of exposure h

**OECD 201** Method

Polyoxypropylendiamin

Polyoxypropylendiamin Reference substance Species Skeletonema costatum

EbC50 141 mg/l

Duration of exposure 2 h Method **DIN EN ISO 10253** 

## 12.2. Persistence and degradability

#### **General information**

not determined

#### 12.3. Bioaccumulative potential

#### **General information**

not determined

## Partition coefficient n-octanol/water (log value)

Remarks not determined

#### 12.4. Mobility in soil

#### **General information**

not determined

#### 12.5. Results of PBT and vPvB assessment

#### General information

not determined

#### 12.7. Other adverse effects

#### **General information**

not determined

### General information / ecology

Do not allow to enter soil, waterways or waste water canal. Avoid release into the atmosphere.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Allocation of a waste code number, according to the European Waste Catalogue (EWC), should be carried out in agreement with the regional waste disposal company.

#### Disposal recommendations for packaging



Date revised: 17.05.2023

Print date: 17.05.2023

Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB

Substance number: 10292 Replaces Version: - / GB

Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

**SECTION 14: Transport information** 

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number or ID number	2735	2735	2735
14.2. UN proper shipping name	POLYAMINES, LIQUID, CORROSIVE, N.O.S. ((Z)- octadec-9-enylamine, Polyoxypropylendiamin)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. ((Z)- octadec-9-enylamine, Polyoxypropylendiamin)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. ((Z)- octadec-9-enylamine, Polyoxypropylendiamin)
14.3. Transport hazard class(es)	8	8	8
Label		3	
14.4. Packing group	П	II	П
Limited Quantity	11	11	
Transport category	2		
14.5. Environmental hazards	ENVIRONMENTALLY HAZARDOUS	Marine Pollutant	ENVIRONMENTALLY HAZARDOUS
		ENVIRONMENTALLY HAZARDOUS	
Tunnel restriction code	E		

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

VOC (EU)

0,39

%

3,6

g/l

# 15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification (Regulation (EC) No. 1272/2008)



Print date: 17.05.2023

Trade name: Hardener S for cds-Mortar 0-3 L flex special

Version: 1 / GB Date revised: 17.05.2023

Substance number: 10292 Replaces Version: - / GB

Skin Corr. 1A H314 Eve Dam. 1 H318 Skin Sens. 1A H317 Repr. 2 H361fd STOT SE 3 H335 STOT RE 1 H372 Asp. Tox. 1 H304 Aquatic Acute 1 H400 Aquatic Chronic 1 H410

# Hazard statements listed in Chapter 2/3

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

#### CLP categories listed in Chapter 2/3

Acute Tox. 3 Acute toxicity, Category 3
Acute Tox. 4 Acute toxicity, Category 4

Aquatic Acute 1 Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic, Category 2
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic, Category 3

Asp. Tox. 1 Aspiration hazard, Category 1 Eye Dam. 1 Serious eye damage, Category 1 Repr. 2 Reproductive toxicity, Category 2 Skin Corr. 1A Skin corrosion, Category 1A Skin Corr. 1B Skin corrosion, Category 1B Skin Corr. 1C Skin corrosion, Category 1C Skin Irrit. 2 Skin irritation, Category 2 Skin sensitization, Category 1 Skin Sens. 1 Skin Sens. 1A Skin sensitization, Category 1A

STOT RE 1 Specific target organ toxicity - repeated exposure, Category 1
STOT RE 2 Specific target organ toxicity - repeated exposure, Category 2
STOT SE 3 Specific target organ toxicity - single exposure, Category 3

#### **Supplemental information**

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.