

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006



Product name : cds-Pouring Concrete UW flex grey  
( Equal for all other colours )

Revision : 09.05.2017

Version (Revision) : 3.0.2 (3.0.1)

Print date : 10.07.2017

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

cds-Pouring Concrete UW flex grey  
Bulk (C499340730)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No Information available

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : cds Polymere GmbH u. Co. KG  
Street/P.O.Box : Gau-Bickelheimer Straße 72  
Country code/Postal code/Town/City : 55576 Sprendlingen/Rhh.  
Telephone : +49 (6701) 9350-0  
Telefax : +49 (6701) 9350-50  
Contact : siehe Kapitel 16 / see chapter 16 / Voir le chapitre 16

### 1.4 Emergency telephone number

cds-Labor / Tel. +49 (67 01) 93 50-28 ( This number is reachable monday to friday from 8 am to 5 pm )

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

#### Regulation (EC) No 1272/2008 (GHS)

Causes skin irritation. · May cause an allergic skin reaction. · Harmful to aquatic life with long lasting effects.  
Aquatic Chronic 3 ; H412 · Eye Irrit. 2 ; H319 · Skin Irrit. 2 ; H315 · Skin Sens. 1 ; H317

### 2.2 Label elements

#### Regulation (EC) No 1272/2008 (GHS)

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard-determining components of labelling

EPOXY RESIN(REAC.PROD.:BISPHENOL A-(EPICHLORHYDRIN),MW<=700) ; CAS-No. : 25068-38-6

1,6 HEXANDIOL-DIGLYCIDYLETHER ; CAS-No. : 16096-31-4

EPOXY RESIN(REAC.PROD.:BISPHENOL F-(EPICHLORHYDRIN),MW<=700) ; CAS-No. : 9003-36-5

Hazard statements

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash contaminated bodyparts thoroughly after handling.

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006



Product name : cds-Pouring Concrete UW flex grey  
( Equal for all other colours )

Revision : 09.05.2017

Version (Revision) : 3.0.2 (3.0.1)

Print date : 10.07.2017

P272 Contaminated work clothing should not be allowed out of the workplace.  
P333/313 If skin irritation or rash occurs: Get medical advice/attention.  
P337/313 If eye irritation persists: Get medical advice/attention.  
P501 Dispose of contents/container to licensed disposal contractor and according to official state regulations.

Special rules for supplemental label elements for certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

## 2.3 Other hazards

None.

## 3. Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

EPOXY RESIN(REAC.PROD.:BISPHENOL A-(EPICHLORHYDRIN),MW<=700) ; Registration number (EC) : 01-2119456619-26-0002 ; EC-No. : 500-033-5; CAS-No. : 25068-38-6

Percentage : 15 - 20 %

Classification 1272/2008 (GHS) : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

EPOXY RESIN(REAC.PROD.:BISPHENOL F-(EPICHLORHYDRIN),MW<=700) ; Registration number (EC) : 01-2119454392-40-0003 ; EC-No. : 500-006-8; CAS-No. : 9003-36-5

Percentage : 2,5 - 5 %

Classification 1272/2008 (GHS) : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

1,6 HEXANDIOL-DIGLYCIDYLETHER ; Registration number (EC) : 01-2119463471-41-0006 ; EC-No. : 240-260-4; CAS-No. : 16096-31-4

Percentage : 1 - 5 %

Classification 1272/2008 (GHS) : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 3 ; H412

POLYOXYPROPYLENDIGLYCIDYLETHER ; CAS-No. : 26142-30-3

Percentage : 1 - 5 %

Classification 1272/2008 (GHS) : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319

METHYL-4-TOLUOLSULFONAT ; EC-No. : 201-283-5; CAS-No. : 80-48-8

Percentage : 1 - 5 %

Classification 1272/2008 (GHS) : Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319  
STOT SE 3 ; H335

For the wording of the listed risk phrases refer to section 16.

## 4. First aid measures

### 4.1 Description of first aid measures

#### General

Immediately remove all contaminated clothing.

#### After inhalation

Call a doctor, should the air passages be affected.

#### After skin contact

Wash away with soap and water and rinse.

#### After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

#### After ingestion

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006



Product name : cds-Pouring Concrete UW flex grey  
( Equal for all other colours )

Revision : 09.05.2017

Version (Revision) : 3.0.2 (3.0.1)

Print date : 10.07.2017

Do not induce vomiting - call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

None.

### 5. Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray.

##### Unsuitable extinguishing media

Waterjet.

#### 5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

#### 5.3 Advice for firefighters

When extinguishing fires, use breathing apparatus with an independent source of air.

#### 5.4 Additional information

Do not allow the quenching water into the sewage system.

### 6. Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Provide for sufficient ventilation. Refer to protective measures listed in sections 7 and 8.

#### 6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

Take-up mechanically and remove according to regulations(Chapter 13).

#### 6.4 Reference to other sections

None.

### 7. Handling and storage

Normal precautions taken when handling chemicals should be observed.

#### 7.1 Precautions for safe handling

##### Information for safe handling

Avoid contact with skin and eyes. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Requirements to be met by storerooms and containers

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

##### Information about separation of incompatible products

Store the foodstuffs separately.

##### Further information about storage conditions

Containers should be kept dry and sealed. Observe recommended storage temperature.

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006



Product name : cds-Pouring Concrete UW flex grey  
( Equal for all other colours )

Revision : 09.05.2017

Version (Revision) : 3.0.2 (3.0.1)

Print date : 10.07.2017

## 7.3 Specific end use(s)

None.

## 8. Exposure controls/personal protection

### 8.1 Control parameters

None.

### 8.2 Exposure controls

#### Personal protective equipment

#### General protective and hygiene measures

Keep away from food, drink and animal feeding stuff. Immediately remove all contaminated clothing. Wash hands before breaks and after work. Normal precautions taken when handling chemicals should be observed.

#### Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn. Filter A/P2

#### Hand protection

Use protective gloves. Plastic Gloves. Only use chemical-protective gloves with CE-labelling of category III. To minimize the wetness in the glove due to perspiration changing of gloves during a shift is required. Check the permeability prior to each renewed use of the glove. Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves : Nitril rubber (NBR) , Fluorocarbon rubber (Viton) . Recommended thickness of the material:  $\geq 0,5$  mm . The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection

Use tightly fitting safety glasses.

#### Body protection

protective clothing.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Image

Form : Solid.  
Colour : Greyish.  
Odour : Poor, characteristic.

#### Relevant safety data

Melting point / melting range :			No data available
Boiling temperature / boiling range :	( 1013 hPa )	>	200 °C
Decomposition temperature :			No data available
Flash point :		>	100 °C
Flammable solids :			Not applicable.
Flammable gases :			No data available.
Oxidising liquids :			No data available.
Lower explosion limit :			No data available
Upper explosion limit :			No data available
Explosive properties :			No data available.
Vapour pressure :	( 50 °C )		not applicable
Density :	( 23 °C )	ca.	2,4 g/cm <sup>3</sup>
Water solubility :	( 20 °C )		No data available
pH value :			No data available
log P O/W :			No data available

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006



Product name : cds-Pouring Concrete UW flex grey  
( Equal for all other colours )

Revision : 09.05.2017

Version (Revision) : 3.0.2 (3.0.1)

Print date : 10.07.2017

---

Viscosity :	( 20 °C )	not applicable
Odour threshold :		No data available
Relative vapour density :	( 20 °C )	No data available
Vapourisation rate :		No data available

## 9.2 Other information

None.

## 10. Stability and reactivity

### 10.1 Reactivity

There are no data available on the product itself.

### 10.2 Chemical stability

There are no data available on the product itself.

### 10.3 Possibility of hazardous reactions

There are no data available on the product itself.

### 10.4 Conditions to avoid

None, if handled according to order.

### 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## 11. Toxicological information

### 11.1 Information on toxicological effects

There are no data available on the product itself.

### 11.2 Experience on practice

In case of contact with the product: danger of resorption through the skin, irritation of skin/mucous membranes. The product has sensitizing effects.

## 12. Ecological information

### 12.1 Toxicity

There are no data available on the product itself.

### 12.2 Persistence and degradability

There are no data available on the product itself.

### 12.3 Bioaccumulative potential

There are no data available on the product itself.

### 12.4 Mobility in soil

There are no data available on the product itself.

### 12.5 Results of PBT and vPvB assessment

There are no data available on the product itself.

### 12.6 Other adverse effects

There are no data available on the product itself.

### 12.7 Additional information

Do not empty into waters or drains.

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006



Product name : cds-Pouring Concrete UW flex grey  
( Equal for all other colours )

Revision : 09.05.2017

Version (Revision) : 3.0.2 (3.0.1)

Print date : 10.07.2017

## 13. Disposal considerations

In accordance with local official regulations. Remove in accordance with regulations.

### 13.1 Waste treatment methods

Waste key

Waste code (91/689/EEC) : 08 01 12

## 14. Transport information

### 14.1 UN number

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

### 14.2 UN proper shipping name

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

### 14.3 Transport hazard class(es)

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

### 14.4 Packing group

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

### 14.5 Environmental hazards

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

### 14.6 Special precautions for user

None.

## 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None.

### 15.2 Chemical safety assessment

There are no data available on the product itself.

## 16. Other information

### Further information

GHS Hazard statements of components

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Department issuing data sheet

cds-Labor

### Contact

Mr. Maouzi , Email : k.maouzi@cds-polymere.de

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006



Product name : cds-Pouring Concrete UW flex grey  
( Equal for all other colours )

Revision : 09.05.2017  
Print date : 10.07.2017

Version (Revision) : 3.0.2 (3.0.1)

---

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

---