



delivery program of cds-epoxy based products

2022

primers / sealers

product name	technical data sheet	description / field of application	hardener	standard packing
cds-Primer colourless consumption: ca. 350 g/m ²	3349	Primer for mineral surfaces	S, FH	25 kg 10 kg
cds-Primer MB consumption: ca. 400 g/m ²	3350	Primer for mineral surfaces, mortar resin for pavements	S, FH	25 kg 10 kg
cds-Sealer BLF consumption: ca. 700 g/m ²	4789	Colored sealer for mineral surfaces	S, FH	25 kg 10 kg

adhesives / mortars

cds-Adhesive consumption: ca. 500 - 800 g/m ²	9900	Used to form an adhesive bridge between concrete and cds-mortars	S, FH, FH-Super*	10 kg 4 kg 2 kg 1 ka
cds-Mortar 0-3 L flex special consumption: ca. 2.000 g/liter	8816	Fast repair of damaged concrete edges and breaks (such as holes) in concrete surfaces.	S, FH, FH-Super**	25 kg 20 kg
cds-V-Mortar flex stable consumption: ca. 2.000 g/liter	8865	Pile grouting of balustrades	S, FH, FH-Super**	25 kg 8 kg
cds-Mortar 0-1 FB consumption: ca. 2.200 g/liter	8846	Concrete repair, kerbstones and stairs repair, production of fillets and ramps	S, FH, FH-Super**	25 kg 20 kg 8 ka
cds-Primer Z consumption: ca. 500 g/m ²	2920	anticorrosive adhesive between steel and cds-mortars	hardener	10 kg 2 kg
cds-Mortar BA consumption: ca. 2.100 g/m ²	8882	Concrete repair of horizontal and low-pitched areas	hardener	25 kg 20 kg
cds-Mortar WHG consumption: ca. 2.100 g/liter	8853	Concrete repair of concrete sealing structures etc	hardener	25 kg 8 kg

coatings inside and outside

cds-Coating HB consumption: ca. 630 - 1500 g/m ²	4400	colored coating for mineral surfaces	hardener	30 kg
cds-Pouring mortar flex consumption: ca. 3000 g/m ²	4224	on concrete floors or cement screeds as a thick layer system	S, FH	284 kg 71 kg
cds-Sealer WE conductive consumption: ca. 200 g/m ²	2910	conductive layer between cds-Primer MB and cds-Coating HB-AS	hardener	20 kg 10 kg

coatings inside and outside

product name		description / field of application	hardener	standard packing
cds-Coating HB-AS consumption: ca. 1.000-1.500 g/m ²	4675	pigmented antistatic coating	S	30 kg
cds-Coating AS consumption: ca. 600 g/m ²	4677	antistatic primer for cds-Coating TS	FH	30 kg

grouts

cds-Pouring Concrete UW consumption: 1.860 g/liter standard colors: grey or black	9910	Easy pourable 2 component epoxy resin material filled with minerals to install in-pavement lights in <u>concrete</u> pavements; fulfills requirements of FAA-guideline AC 150/5370-10, Item P-606.	S, FH	8 kg
cds-Pouring Concrete UW rapid consumption: 1.930 g/liter standard colors: grey or black	9915	Quick curing alternative for UW For temperatures from +5°C to +15°C, stressable at +10 °C after 2 hours, fulfills requirements of FAA-guideline AC 150/5370-10, Item P-606.	S, FH	8 kg
cds-Pouring Concrete UW flex consumption: 1.740 g/liter standard colors: grey or black	9932	Flexible alternative for UW / UW rapid to install in-pavement lights in <u>asphalt or concrete</u> pavements, fulfills requirements of FAA-guideline AC 150/5370-10, Item P-606.	FH	8 kg
cds-Pouring Concrete UW ultra consumption: 1.770 g/liter standard colors: grey or black	9930	more reactive alternative for UW/ UW rapid to install in-pavement lights in <u>asphalt or concrete</u> pavements, limited use between + 1 °C to + 15 °C.	hardener	6,5 kg
cds-Cable-Joint-Filler consumption: 1.800 g/liter standard colors: grey or black	9945	Filling of cable ducts cut in asphalt concrete and concrete surfaces (not applicable for expansion joints).	S, FH, FH-Super*	10 kg

Hardeners: S = standard FH = faster FH-Super = quick
Standard colors for colored sealers and coatings, if not differently named:
ca. RAL 1019, 7023, 7030, 7032, 7035, 7037, 7038.

Information on further products for sealings, coatings, concrete repair, etc. on request.



Extract of our conditions of sales

Our prices are calculated FCA Sprendlingen, Germany.
Prices include standard packaging and hardener. Europallets, sea- or airfreight packaging, DGD, packing list and export application charged separately.
Prices and conditions for products in special colours on request.
Our terms of delivery are based on Incoterms® 2020, ICC.
Our general conditions of payment are: payment in advance or, if preferred, for orders > 25.000 €, confirmed and irrevocable L/C. Fees for the LC will be charged to the customer.
Taxfree as intra-community delivery only under the prerequisite of valid VAT Identity No. and stamped and signed confirmation of arrival provided by the customer. Without confirmation of arrival VAT will be charged!
For technical information about our products please read carefully our technical data sheets, which are at your disposal.
Any order is based on our general terms and conditions which will be sent on request.

With publication of this price list all previous price lists are void.

cds Polymere GmbH & Co. KG
Gau-Bickelheimer Straße 72
55576 Sprendlingen/Rhh.
Germany

Tel. +49 6701 9350-0
Fax +49 6701 9350-50
www.cds-polymere.de
info@cds-polymere.de

managing director
Dr.-Ing. Peter Scharf

Local Court Mainz HRA 41646
partner liable to unlimited extent: cds Polymere Verwaltungs GmbH, Sprendlingen, Local Court Mainz, HRB 43925

